

# De-Foaming Agent

## ANTI-FOAM SP-505

---

### DESCRIPTION

**Anti-Foam SP-505** is recommended for use in Coating Color and Size-Press.

**Anti-Foam SP-505** will eliminate existing foam, and also remain in the water to prevent further foam build-up

### APPLICATION

- Input Value : Using about 0.1 - 1 part per Binder content (Dry Base)

### STORAGES

- Avoid direct rays of light & high temperatures
- Storage indoors at 5 – 30°C
- Local ventilation is recommended.
- Sediments and separation are possible, before using, must shake well and enough.
- Additional handling information is contained in the material safety data sheet which is available on request.

### PHYSICAL PROPERTIES

- Active Content : > 55%
- Viscosity (cps, at 20°C) : < 5,000cps
- pH(at 25°C) : 9.0 ± 1
- Appearance : White and opaque liquid.
- Ionic character : Anionic
- Solubility : Easy to mix with WATER

**EN-TECH POLYMER CO., LTD.**

Rm209, Jeil Plaza, Imae Dong 131-1, Bun Dang Ku, Seong nam City, Kyunggi Do, 463-806, South Korea.  
TEL : 82-31-7067452 FAX : 82-31-7067453 [www.ntechpolymer.com](http://www.ntechpolymer.com)