

Crepe Control Modifier

NTCREPE AP-100

DESCRIPTION

NTCREPE AP-100 is a high performance crepe control modifier in an aqueous solution.

APPLICATION

NTCREPE AP-100 is used to enhance the crepe control operation and provide the proper balance for effective creping. It may be added separately or formulated within the NTCREPE adhesive products.

ADVANTAGES

- Improves Yankee coating uniformity
- Increases coating drying on high speed machines
- *Enables effective crepe at higher sheet moisture conditions
- Increases doctor blade and Yankee dryer life

USE REQUIREMENTS

NTCREPE AP-100 is applied through the spray boom on to the Yankee dryer surface at a dosage range 0.25 to 10% of coating solids.

PHYSICAL PROPERTIES

Appearance	Clear liquid
pH (concentrate)	3.0 - 5.0
Density (lb./gal. @72°F)	9.24
Shelf Life	6 months
Freeze Point	0°C
Active Contents	73%
Solubility	Soluble in water

EN-TECH POLYMER CO., LTD.

Rm209, Jeil Plaza, Imae Dong 131-1, Bun Dang Ku, Seong nam City, Kyunggi Do, 463-806, South Korea.
TEL : 82-31-7067452 FAX : 82-31-7067453 www.ntechpolymer.com