

SPECIFICATION SHEET



The listed values are exemplary figures. Exact parameters are set individually according to the specific requirements of each paper machine.

FABRIC TYPE

<u>Fabric Type</u>		TriplexTop W 3-layer		
<u>Fabric Structure</u>	<u>Description</u>	<u>Mesh Number</u> [1/cm]	<u>Diam.</u> [mm]	<u>Material</u>
	Warp	30	0,13	PET
	Warp	30	0,21	PET
	Upper Weft	39	0,13+0,13	PET/PA
	Lower Weft	26	0,27	PET/PA

TECHNICAL DATA

<u>Warp yarns</u>	60 /cm	<u>T-Count</u>	69
<u>Top</u>	30 /cm	<u>Caliper</u>	0,87 mm
<u>Bottom</u>	30 /cm	<u>Critical Caliper*</u>	0,60 mm
<u>Weft yarns</u>	65 /cm	<u>Fiber Support Index</u>	184
<u>Top</u>	39 /cm	<u>Drainage Index</u>	31,7
<u>Bottom</u>	26 /cm	<u>Optional</u>	V-POWERLINE
<u>Air Permeability</u>			
<u>at 125 Pa</u>	320 cfm		
<u>Elongation (100 N/cm)</u>	0,87 %		

BENEFITS FOR THE PAPERMAKER

- Plain weave paper side
- Proven quality for speciality paper applications
- Optimum life potential
- Gentle dewatering
- High retention with reduced tendency to fibre carrying

* the critical caliper serves as reference value. The final lifetime is individual and can only be determined visually

December 9, 2020 iv